



GENERAL SPECIFICATIONS

Resistencia al fuego / Classement feu Fire classification / Resistenza al fuoco	-
Certificación Ambiental / Certification Environnementale Environmental Certification / Certificazione ambientale	Oekotex / Greenguard
Absorción acústica / Absorption acoustique Sound absorption / Assorbimento acustico - (ISO 10534:2)	-



TECHNICAL DATA

Composición / Composition Composition / Composizione	100 % PES Foamed Coating
Ancho de rollo / Largeur rouleau Roll width / Larghezza del tessuto	300
Grado de apertura / Coefficient d'ouverture Openess Factor / Grado di apertura	0%
Espesor / Épaisseur Thickness / Spessore	0,35
Peso / Poids Weight / Peso	300g/m2
Resistencia a la luz / Resistance a la lumiere Light Fastness / Resistenza alla luce - (Grey Scale / Blue Scale)	- / Class 4-5
Resistencia al desgarro / Résistance à la déchirure Tear resistance / Resistenza alla rottura - (EN ISO 13937-3)	185 daN - 175 daN
Resistencia a la ruptura / Résistance à la rupture Tensile strength / Resistenza alla rottura - (EN ISO 13934-1)	-



SOLAR HEAT CONTROL PROPERTIES

Ref.	Description	Termal Factors			Optical Factors			Gtot		Transmision UV	Martindale Test
		Ts	Rs	As	Tv	Rv	Av	Gt	Fc		
40501	WHITE	-	-	-	-	-	-	-	-	-	-
40503	LIGHT GREY	-	-	-	-	-	-	-	-	-	-
40504	IVORY	-	-	-	-	-	-	-	-	-	-
40502	BEIGE	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-