



TECHNICAL DATA

Composición / Composition Composition / Composizione	80% PVC + 20% PES
Ancho de rollo / Largeur rouleau Roll width / Larghezza del tessuto	250 cm / 98 "
Grado de apertura / Coefficient d'ouverture Openess Factor / Grado di apertura	14%
Espesor / Épaisseur Thickness / Spessore	0,56 mm ± 5% / -
Peso / Poids Weight / Peso	337 gr/m² ± 5% / -
Resistencia al fuego / Classement feu Fire classification / Resistenza al fuoco	Class 1 : EN 13773. (CI) / NFPA 701 : Pass / CAN/ULC-S109-03 : Pass
Certificación Ambiental / Certification Environnementale Environmental Certification / Certificazione ambientale	Greenguard
Absorción acústica / Absorption acoustique Sound absorption / Assorbimento acustico - (ISO 10534:2)	-
Resistencia a la luz / Resistance a la lumiere Light Fastness / Resistenza alla luce - (Grey Scale / Blue Scale)	5/5 - 4/5 White / 8/8 - 7/8 White
Resistencia al desgarro / Résistance à la déchirure Tear resistance / Resistenza alla rottura - (EN ISO 13937-3)	3,9 daN - 2,7 daN
Resistencia a la ruptura / Résistance à la rupture Tensile strength / Resistenza alla rottura - (EN ISO 13934-1)	138,6 daN - 82,6 daN

*Uso exterior solo en tendina

OTHER CERTIFICATIONS



WASHING INSTRUCTIONS



FABRIC COLOURS

